

TriadSim Vignette

Min Shi

2017-05-12

TriadSim is a package that can simulate genotypes for case-parent triads, case-control, and quantitative trait samples with realistic linkage disequilibrium structure and allele frequency distribution. For studies of epistasis one can simulate models that involve specific SNPs at specific sets of loci, which we will refer to as “pathways”. *TriadSim* generates genotype data by resampling triad genotypes from existing data. It takes genotypes in PLINK format as the input files. The genotypes for the mothers, fathers, and children are in separate files. The mothers, fathers, and children must be from the same set of triad families although the ordering of the families can be different for the three sets of data. After reading in the genotypes, a sorting step will reorder the families so that the three individuals in each family can realign.

Main function `TriadSim`

`TriadSim` is the main function to perform the simulations. The example function call below simulates genotype data for 1000 case-parent triads for 4 chromosomes (chromosomes 1, 8 17, 20) under a genetic main effect scenario with a baseline disease prevalence of P0=0.001 and genetic relative risks of 1.5 and 2 for carrying the first and the second pathway respectively. This function call will write output files in PLINK. The output file names and path to the directory are given by the parameter “out.put.file” and the chromosome number. Each set (.bim, .bed and .fam files) of PLINK files contain genotype data for one chromosome for all simulated samples. The name of the file is the concatenation of the value of the input parameter “out.put.file” and chromosome number. For example, if “out.put.file” is set to be “triad”, the names of the output files will be triad1, triad8, triad17 and triad20 for our example. See R package documentation for more details.

```
library(TriadSim)
m.file <- file.path(system.file(package = "TriadSim"), 'extdata/pop1_4chr_mom')
f.file <- file.path(system.file(package = "TriadSim"), 'extdata/pop1_4chr_dad')
k.file <- file.path(system.file(package = "TriadSim"), 'extdata/pop1_4chr_kid')
input.plink.file <- c(m.file, f.file, k.file)

TriadSim(input.plink.file, out.put.file=file.path(tempdir(), 'triad'), fr.desire=0.05, pathways=list(1:4))

## [1] 21 118 121 140 155 168 218 383
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/triad1.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/triad1.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/triad1.bed (SNP-major mode)
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/triad8.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/triad8.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/triad8.bed (SNP-major mode)
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/triad17.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/triad17.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/triad17.bed (SNP-major mode)
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/triad20.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/triad20.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/triad20.bed (SNP-major mode)
```

The following call simulates a quantitative trait (by setting “qtl=T”). The function will create 4 sets of plink files, one for each chromosome.

```
TriadSim(input.plink.file, file.path(tempdir(), 'qtl'), fr.desire=0.3, pathways=list(1:4,5:8), n.ped=1000)
```

```
## [1] 72 95 139 145 247 276 279 339
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/qtl1.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/qtl1.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/qtl1.bed (SNP-major mode)
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/qtl8.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/qtl8.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/qtl8.bed (SNP-major mode)
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/qtl17.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/qtl17.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/qtl17.bed (SNP-major mode)
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/qtl20.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/qtl20.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/qtl20.bed (SNP-major mode)
```

The following call simulates a scenario that involves gene-environment interaction. The relative risk for the exposure main effect is 1.2. The relative risks for carrying the first and second pathway SNPs are 1.5 and 2 respectively for the exposed individuals and are 1 and 1 for the unexposed individuals.

```
TriadSim(input.plink.file, file.path(tempdir(), 'gxe'), fr.desire=0.3, pathways=list(1:4,5:8), n.ped=1000)
```

```
## [1] 72 95 139 145 247 276 279 339
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/gxe1.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/gxe1.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/gxe1.bed (SNP-major mode)
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/gxe8.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/gxe8.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/gxe8.bed (SNP-major mode)
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/gxe17.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/gxe17.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/gxe17.bed (SNP-major mode)
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/gxe20.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/gxe20.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/gxe20.bed (SNP-major mode)
```

The following call simulates a stratified scenario that involves gene-environment interaction. The risk parameters are the same as the scenario above. The “input.plink.file” is a list of two character vectors. Each vector contains three character strings giving the directory and basename of the PLINK files in one subpopulation. The subpopulations are equally sized (pop1.frac=0.5). The baseline disease prevalence (disease prevalence in the unexposed who carries 0 copy of the risk pathway) is 0.001 in the first subpopulation while

that in the second subpopulation is 0.003 (0.001*3). The exposure prevalence in the two subpopulations are 0.1 and 0.3 respectively.

```
library(TriadSim)
m.file <- file.path(system.file(package = "TriadSim"), 'extdata/pop1_4chr_mom')
f.file <- file.path(system.file(package = "TriadSim"), 'extdata/pop1_4chr_dad')
k.file <- file.path(system.file(package = "TriadSim"), 'extdata/pop1_4chr_kid')
m.file2 <- file.path(system.file(package = "TriadSim"), 'extdata/pop2_4chr_mom')
f.file2 <- file.path(system.file(package = "TriadSim"), 'extdata/pop2_4chr_dad')
k.file2 <- file.path(system.file(package = "TriadSim"), 'extdata/pop2_4chr_kid')
input.plink.file2 <- list(c(m.file, f.file, k.file), c(m.file2, f.file2, k.file2))

TriadSim(input.plink.file2, out.put.file=file.path(tempdir(), 'stratified') , fr.desire=0.3,pathways=list(1:3,4:6))

## [1] 72 95 139 145 247 276 279 339
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu\stratified1.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu\stratified1.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu\stratified1.bed (SNP-major mode)
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu\stratified8.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu\stratified8.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu\stratified8.bed (SNP-major mode)
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu\stratified17.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu\stratified17.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu\stratified17.bed (SNP-major mode)
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu\stratified20.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu\stratified20.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu\stratified20.bed (SNP-major mode)
```

To simulate case-control data the function needs to be called twice, calls to simulate cases (is.case=TRUE) and controls (is.case=FALSE) respectively. The script below calls the function to simulate 1000 cases and 1000 controls and writes genotypes of the cases and controls into separate sets of PLINK files.

```
## cases
TriadSim(input.plink.file,file.path(tempdir(),'case') , fr.desire=0.05,pathways=list(1:4,5:8),n.ped=1000)

## [1] 21 118 121 140 155 168 218 383
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu\case1.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu\case1.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu\case1.bed (SNP-major mode)
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu\case8.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu\case8.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu\case8.bed (SNP-major mode)
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu\case17.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu\case17.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu\case17.bed (SNP-major mode)
## coercing object of mode numeric to SnpMatrix
```

```

## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/case20.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/case20.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/case20.bed (SNP-major mode)

## controls
TriadSim(input.plink.file, file.path(tempdir(), 'ctrl'), fr.desire=0.05, pathways=list(1:4,5:8), n.ped=10)

```

```

## [1] 21 118 121 140 155 168 218 383
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/ctrl1.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/ctrl1.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/ctrl1.bed (SNP-major mode)
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/ctrl8.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/ctrl8.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/ctrl8.bed (SNP-major mode)
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/ctrl17.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/ctrl17.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/ctrl17.bed (SNP-major mode)
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/ctrl20.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/ctrl20.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/ctrl20.bed (SNP-major mode)

```

Some additional details

The source data may contain genotyping errors that cause non-Mendelian inheritance patterns. For these non-Mendelian families, genotypes of the three individuals in the family will be set to missing at the corresponding SNPs. We assume nonpaternity and adoption have both been ruled out in QC for the source data.

This function requires at least two pathway SNPs, either two SNPs in the one pathway or two pathways each involving one SNP. If the users are interested in a single SNP scenario one can trick the function by setting the number of pathway to 2, each with a single SNP in the pathway but only the SNP in the first pathway carries a risk while that in the second pathway does not change risk. See below for an example.

```

TriadSim(input.plink.file, file.path(tempdir(), 'singleSNP'), fr.desire=0.05, pathways=list(1,2), n.ped=10)

```

```

## [1] 118 140
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/singleSNP1.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/singleSNP1.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/singleSNP1.bed (SNP-major mode)
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/singleSNP8.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/singleSNP8.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/singleSNP8.bed (SNP-major mode)
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/singleSNP17.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/singleSNP17.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/singleSNP17.bed (SNP-major mode)
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/singleSNP20.fam

```

```
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/singleSNP20.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/singleSNP20.bed (SNP-major mode)
```

Facility functions

The following set of functions is provided in case users want to have more control over the simulation parameters. They are called by the main function to generate simulations. Users do not need to call them directly.

`pick_target.snp`

Users can manually pick the target SNPs in the pathway or use the facility function `pick_target.snp` to pick the set of target SNPs in the pathway(s) based on a desired allele frequency. The example below uses the example files that come with the package to select 8 SNPs with allele frequencies close to 0.05. The function returns the selected target SNPs by giving the row numbers (i.e., the order) of the corresponding SNPs among all the SNPs in the associated “bim” file. For example a return of “1084 2044 3285 4016 5117 6067 7077 8187” means the SNPs at rows 1084 2044 3285 4016 5117 6067 7077 8187 are selected to be the target SNPs in the pathway.

```
m.file <- file.path(system.file(package = "TriadSim"), 'extdata/pop1_4chr_mom')
f.file <- file.path(system.file(package = "TriadSim"), 'extdata/pop1_4chr_dad')
picked.target <- pick_target.snp(c(m.file,f.file),0.05, 8)
```

```
## [1] 21 118 121 140 155 168 218 383
cat('Target SNPs picked:',picked.target[[2]], '\n')
```

```
## Target SNPs picked: 21 118 121 140 155 168 218 383
```

`get.target.geno`

The function `get.target.geno` retrieves genotypes of the target SNPs and returns the genotypes of the triads in a list of three elements: the observed genotypes of the mothers from family 1 to family n repeated twice, genotypes of the fathers from family 1 to family n repeated twice and genotypes of children from family 1 to n followed by (stacking on top of) genotypes of the complements in the same family order.

```
target.snp <- picked.target[[2]]
m.file <- file.path(system.file(package = "TriadSim"), 'extdata/pop1_4chr_mom')
f.file <- file.path(system.file(package = "TriadSim"), 'extdata/pop1_4chr_dad')
k.file <- file.path(system.file(package = "TriadSim"), 'extdata/pop1_4chr_kid')
# the preloaded data frame snp.all2 contains the data frame read from the corresponding .bim file.
target.geno <- get.target.geno(c(m.file,f.file,k.file), target.snp,snp.all2)
```

The output `target.geno` is a list of three elements, each being a matrix of genotypes

```
length(target.geno)
```

```
## [1] 3
```

For this example the genotypes form a 2000 x 8 numerical matrix (2x1000 families and 8 SNPs)

```

mom.target <- target.geno[[1]]
dad.target <- target.geno[[2]]
kid.target <- target.geno[[3]]
str(mom.target)

## num [1:2000, 1:8] 1 2 2 2 2 2 2 2 0 ...

```

To increase diversity, TriadSim introduces break points at each chromosome, selecting them independently for each triad being simulated. The break points can be picked manually or using the function `get.brks`. The function tends to pick the break points at recombination hotspots if such data are passed in as an input parameter `rcmb.rate`.

```

found.brks <- get.brks(N.brk=3,n.ped=1000, snp.all2, target.snp,rcmb.rate=rcmb.rate)
breaks <- found.brks[[1]]
family.position <- found.brks[[2]]

```

This function returns a list of two items. The first is a 1000 x 17 matrix of integers showing where the chromosomal breaks are to take place (in terms of the order of the SNPs in the PLINK files) for each individual in the simulated trios. Each chromosome has 3 breaks, adding to that is the number of breaks between chromosomes, i.e., 3, and the first and the last SNPs, and this is where the 17 comes from. Here 1000 denotes the number of triads in the simulated data as defined by the `n.ped` input parameter.

```

dim(breaks)

## [1] 1000 19

head(breaks)

##      [,1] [,2] [,3] [,4] [,5] [,6] [,7] [,8] [,9] [,10] [,11] [,12] [,13]
## [1,]    0   41  119  129  147  159  173  181  215  257  297  300  324
## [2,]    0  102  120  123  143  165  173  197  215  266  297  311  326
## [3,]    0   21  118  123  143  166  173  183  228  256  297  300  332
## [4,]    0   76  118  137  146  162  173  192  248  266  297  313  324
## [5,]    0   27  118  123  151  161  173  183  243  259  297  313  326
## [6,]    0  101  118  137  147  164  173  202  245  262  297  306  322
##     [,14] [,15] [,16] [,17] [,18] [,19]
## [1,]  338  355  360  377  407  412
## [2,]  346  355  360  377  407  412
## [3,]  337  355  362  376  407  412
## [4,]  349  355  360  384  408  412
## [5,]  347  355  360  381  404  412
## [6,]  338  355  361  377  408  412

```

The second one is a 1000 x 8 matrix showing the chromosomal segments out of which each target SNP is selected for each simulated trio.

```
dim(family.position)
```

```
## [1] 1000 8
```

```

head(family.position)

##      [,1] [,2] [,3] [,4] [,5] [,6] [,7] [,8]
## [1,]    1    2    3    4    5    6    9   17
## [2,]    1    2    3    4    5    6    9   17
## [3,]    1    2    3    4    5    6    8   17
## [4,]    1    2    3    4    5    6    8   16
## [5,]    1    2    3    4    5    6    8   17
## [6,]    1    2    3    4    5    6    8   17

```

```
fit.risk.model.par
```

`fit.risk.model.par` is a function that resamples families based on the specified risk model. It can simulate a homogenous scenario or a stratified scenario with two subpopulations. The risk model can involve exposure main effects as well as gene by exposure interactions. This function is parallelized to shorten the running time. An example call for simulating a binary phenotype is given below.

```

betas <- c(-6.4, 3.2, 5.8)
pwy <- list(1:4, 5:8)
## scenarios of genetic main effects only for a binary phenotype
fitted.model1 <- fit.risk.model.par(n.ped=1000, brks=breaks, target.snp, fam.pos=family.position,
mom.tar=mom.target, dad.tar=dad.target, kid.tar=kid.target, pathways=pwy,
betas, e.fr=NA, betas.pop1.frac= NA, rate.betas=NA, qtl= FALSE, out.put.file=file.path(tempdir(), 'riskmodel1'))

```

This function returns a list of five items. For a scenario involving a binary trait in a homogeneous population and no gene-environment interaction only the first two items contain the data needed. The first is a 1000 x 16 matrix of integers showing which source families are picked for each chromosomal segments in each of the 1000 simulated trios.

```

sel.fam <- fitted.model1[[1]]
colnames(sel.fam) <- paste('seg', 1:ncol(sel.fam), sep="_")
rownames(sel.fam) <- paste('fam', 1:nrow(sel.fam), sep="_")
dim(sel.fam)

```

```
## [1] 1000 18
```

```
head(sel.fam)
```

```

##      seg_1 seg_2 seg_3 seg_4 seg_5 seg_6 seg_7 seg_8 seg_9 seg_10 seg_11
## fam_1    816   102   107   956  1055   683  1865  1960  1817  1240  1894
## fam_2    252  1619   498   332   965  1822   403   292  1368   529   280
## fam_3   1723  1130   976   733   290  1513  1565  1943  1592   156   522
## fam_4    212     50  1524  1965   906   626   503   504   493    38   927
## fam_5   1844  1161  1582   189  1211   253  1789   289   826   463   620
## fam_6   1157  1643  1831  1851   276   608   242   188  1609   818   488
##      seg_12 seg_13 seg_14 seg_15 seg_16 seg_17 seg_18
## fam_1     884   1217   1212   1866   1322   1820    948
## fam_2     721    119    378   1766   1868   1384   1768
## fam_3     283    389    877   949   1340   492    753
## fam_4     429    349   1031   1147   622   1522   426
## fam_5    1340    210   1921   553   1386   1098   413
## fam_6    1528   1572   1723   1307   1285   986   1659

```

The second one is a 1000 x 8 matrix showing the genotypes at the 8 target SNPs.

```
sim.pathway.geno <- fitted.model1[[2]]
colnames(sim.pathway.geno) <- paste('target.snp', 1:ncol(sim.pathway.geno), sep="_")
rownames(sim.pathway.geno) <- paste('fam', 1:nrow(sim.pathway.geno), sep="_")
dim(sim.pathway.geno)

## [1] 3000     8

head(sim.pathway.geno)

##      target.snp_1 target.snp_2 target.snp_3 target.snp_4 target.snp_5
## fam_1          2          2          2          2          2
## fam_2          2          2          2          2          2
## fam_3          2          2          2          2          2
## fam_4          2          2          2          2          2
## fam_5          2          2          2          2          2
## fam_6          2          2          2          2          2
##      target.snp_6 target.snp_7 target.snp_8
## fam_1          2          2          2
## fam_2          2          2          2
## fam_3          2          2          2
## fam_4          2          2          2
## fam_5          2          2          2
## fam_6          2          2          0
```

The following is an example call for a scenario involving gene-environment interaction for a binary phenotype.

```
## a scenario of gene-environment interaction for a binary phenotype
betas.e <- c(-6.4, 3.9, 6.5)

fitted.model2 <- fit.risk.model.par(n.ped=1000, brks=breaks, target.snp=family.position,
mom.tar=mom.target, dad.tar=dad.target, kid.tar=kid.target, pathways=pwy,
betas, e.fr= 0.2, betas.e, pop1.frac= NA, rate.beta=NA, qtl= FALSE, out.put.file=file.path(tempdir(), 'riskmodel2'))
```

For this scenario the third returned item contains exposure data.

```
exposure <- fitted.model2[[3]]
table(exposure)
```

```
## exposure
##   0   1
## 781 219
```


The following is an example call for a quantitative trait scenario.

```
## scenarios of a quantitative trait phenotype
fitted.model3 <- fit.risk.model.par(n.ped=1000, brks=breaks, target.snp=family.position,
mom.tar=mom.target, dad.tar=dad.target, kid.tar=kid.target, pathways=pwy,
betas, e.fr=NA, betas.pop1.frac= NA, rate.beta=NA, qtl=TRUE, out.put.file=file.path(tempdir(), 'riskmodel3'))
```

For this scenario the fifth returned item contains data for the quantitative phenotype.

```
qt.pheno <- fitted.model3[[5]]
hist(qt.pheno, main='Histogram of Simulated Quantitative Trait', xlab='QT')
```

Histogram of Simulated Quantitative Trait



```
glue.chr.segment.par
```

`glue.chr.segment.par` is a function that splices the triad chromosomal segments into “complete” trios. The spliced trio sets are written into separate plink files chromosome by chromosome. It is parallelized and if no “no_cores” value is given half of the total number of CPUs available will be used in the parallelization.

```
glue.chr.segment.par(c(m.file,f.file,k.file),file.path(tempdir(),'triad'), breaks,sel.fam,snp.all2,sim.p)

## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/triad1.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/triad1.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/triad1.bed (SNP-major mode)
```

```
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/triad8.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/triad8.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/triad8.bed (SNP-major mode)
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/triad17.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/triad17.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/triad17.bed (SNP-major mode)
## coercing object of mode numeric to SnpMatrix
## Writing FAM file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/triad20.fam
## Writing extended MAP file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/triad20.bim
## Writing BED file to C:\Users\shi2\AppData\Local\Temp\2\RtmpgjUBeu/triad20.bed (SNP-major mode)
```