


Prestige 201

High Speed Internet Access

The Prestige 201's Single User Account(SUA) / Network Address Translation(NAT) enables multiple workstations on the local area network to access the Internet for the cost of only one IP address. This router allows maximum speed of up to 128Kbps and supports CAPI applications over the LAN.



ISO 9001 Certified.



This product is based on the ZyNOS Networking Operating System with free firmware upgrades that can be downloaded as they become available.

Specifications are subject to change without notice.

All trademarks are the property of their respective owners.

ZyXEL

TOTAL INTERNET ACCESS SOLUTION

Physical Interface

- One RJ-45 port for ISDN connection
- One Four-port 10M Hub for Ethernet LAN connection
- One RS-232 Console Port for local configuration and management



International:
ZyXEL Communications Corp.
Tel: 886-3-5783942
Fax: 886-3-5782439
E-mail: sales@zyxel.com.tw
support@zyxel.com.tw
Web: http://www.zyxel.com

North America:
ZyXEL Communications, Inc.
Tel: 714-632-0882
Fax: 714-632-0858
E-mail: sales@zyxel.com
support@zyxel.com
Web: http://www.zyxel.com

Scandinavia:
ZyXEL Communications A/S
Tel: 45-3955-0700
Fax: 45-3955-0707
E-mail: sales@zyxel.dk
support@zyxel.dk
Web: http://www.zyxel.dk

Germany:
ZyXEL Deutschland GmbH.
Tel: +49-2405-6909-0
Fax: +49-2405-6909-99
E-mail: sales@zyxel.de
support@zyxel.de
Web: http://www.zyxel.de

Austria:
ZyXEL Communications Services GmbH.
Tel: +43-1-4948677-0
Fax: +43-1-4948678
E-mail: sales@zyxel.at
support@zyxel.at
Web: http://www.zyxel.at

Prestige 201

ISDN Internet Access Router



The Prestige 201 is ZyXEL's latest ISDN router especially designed for fair and friendly Internet Access. The built-in 10M four-port hub allows multiple PC to connect to the Internet for the cost of a single ISP account. The Prestige Network Commander, ZyXEL's user-friendly windows-based configurator software, makes configuration as easy as clicking "Next". It is an economic and convenient router for your office.

ISDN Network Compatibility

- ISDN BRI (Basic Rate Interface)-Two 64Kbps B channels
- Supports DSS1 for Europe and Asia
- Standard BRI S/T interface
- ISDN leased line capability with 64K or 128Kbps transmission rate
- Caller ID

Internet Access & Dial Up Features

- Point-to-Point Protocol(PPP)/Multilink Point-to-Point(MP) support
- Dial-on-Demand
- Bandwidth-on-Demand allocates bandwidth when needed
- SUA(Single User Account)/NAT(Network Address Translation) enables multiple workstations on the LAN to access the Internet for the cost of a single ISP account
- DNS Proxy supports IPCP (IP Control Protocol) extension to get DNS (Domain Name System) server addresses and reply automatically to client DNS requests
- BACP/BAP support to manage the number of links in a multilinked bundle
- Hi/fin®(Stac® LZS) compression support
- Dial-up to the Internet automatically with call scheduling
- NetCAPI allows G3/G4 FAX transmission, Euro File Transfer, Autoanswer host and Telephony over the LAN(Supports DSS1 only)

Network Protocols

- IP Protocol routing

Network Management

- Windows-based Configurator software for quick configuration
- Menu driven user interface for easy network management
- Local and remote console management
- TFTP/FTP firmware upgrade and configuration backup and restore
- DHCP (Dynamic Host Configuration Protocol) server automatically assigns IP addresses to Windows 95/98/NT and other systems that support DHCP client
- Call Bumping
- Call Detail Records feature provides efficient tracking of outgoing calls
- Call Control Management: Blacklist, Call Budget, and Call History
- Built-in diagnostic and remote support tools

Robust Security Features

- Password Protected System Management Terminal
- Password Authentication Protocol (PAP)
- Challenge Handshake Authentication Protocol (CHAP)
- MS CHAP
- Packet Filtering for controlled access from your network

Other

- Dimension: 230mm(W) x 161mm(L) x 35mm(H)
- Operating Environment: Temperature :0 C-50 C; Humidity: 20-95 %
- Storage Environment: Temperature: -30-60 C; Humidity: 20-95 %
- Power Requirement: 12VDC
- Weight: g

Two Years Warranty